



**TONGYI POWER  
ZHEJIANG PLANT**

Xietang Town,  
Shangyu City, 312369  
Zhejiang, P.R.China  
T: 86.575.82072584  
F: 86.575.82078631  
tongyi@zjtongyi.com  
zjtongyi@yeah.net  
www.zjtongyi.com

**TONGYI POWER  
HUBEI FACTORY**

Chengnan Industrial  
Development Zone,  
Jinzhou City, 434100  
Hubei, P.R.China  
T: 86.716.8022566  
F: 86.716.8022966  
www.hbtydq.com

Request a quote or  
want customized size,  
please send a drawing  
via e-mail or call us.

## Pultrusion Profile

### Profile Availability List - Metric (MM)

Features & benefits of Fiberglass  
Pultruded Rod:

- Corrosion resistant
- Non-conductive thermally and electrically
- Non-magnetic electromagnetic transparency
- Light weight
- High strength
- Dimensional stability
- Long life cycle
- Low maintenance

Available Grades:


Class "F"  
Fiberglass  
Epoxy Resin  
WHVRI Test Report  
Insulation systems  
for 155 °C

Class "H"  
Fiberglass  
Epoxy Resin  
WHVRI Test Report  
Insulation systems  
for 180°C

Other Grades:

Fiberglass  
Polyester Resin  
Class C - 120 °C

#### Rectangular bar

	10 × 22
	10 × 30
	14 × 22
	16 × 22
	16 × 30
	20 × 30
	20 × 40
	25 × 50
	30 × 50
	40 × 50
	40 × 60
	50 × 50
	60 × 60

#### Channel



	50 × 32 × 5
	55 × 28 × 4
	63 × 30 × 3
	70 × 30 × 3.8
	70 × 30 × 4.5
	80 × 30 × 3
	80 × 30 × 5
	88 × 35 × 5
	94.5 × 20 × 2.8
	96 × 20 × 2.8
	110 × 60 × 10
	180 × 50 × 6
	180 × 50 × 8

#### Round Rod



	D 6
	D 8
	D10
	D12
	D16
	...
	...
	D90

#### Dogbone



	8 × 6 × 3
	10 × 8 × 4
	12 × 10 × 5
	13 × 10 × 6.9
	16 × 10 × 5.3
	19 × 10 × 6.1
	19 × 12 × 6.1

#### Angle



	30 × 30 × 5.1
	35 × 35 × 5.1
	40 × 40 × 2.5
	40 × 40 × 4
	45 × 45 × 5.1
	50 × 20 × 3
	50 × 50 × 5
	50.8 × 50.8 × 6.35
	75 × 20 × 3
	75 × 75 × 6
	75 × 75 × 9.5
	76 × 76 × 6.35
	76 × 76 × 9.53
	76 × 43 × 3
	76.2 × 76.2 × 6.35
	76.2 × 76.2 × 8
	100 × 100 × 9.5
	101 × 101 × 9.5
	101.6 × 101.6 × 12.7
	125 × 125 × 10
	152 × 152 × 9.53
	152 × 152 × 12.7

